

IPSC Shotgun equipment rules:

Open Division

1	Minimum power factor	480
2	Minimum shot weight	No
3	Minimum caliber	20 gauge / 20 bore
4	Maximum shotgun weight	No
5	Minimum trigger pull	No
6	Restriction on action types	No
7	Magazine length restrictions	No
8	Detachable magazines	Permitted
9	Magazine capacity restrictions	No
10	Speed loading devices	Permitted
11	Modifications/attachments to loading port floor plate	Permitted
12	Compensators, sound and/or flash suppressors	Permitted
13	Ports	Permitted
14	Optical or Electronic sights	Permitted
15	Barrel heat shields	Permitted
16	Maximum overall length for complete gun	No restriction
17	Modifications allowed	Yes
18	Factory produced guns only (minimum 100 units)	No

Special Conditions:

19. Prototypes are allowed.

Standard Division

1	Minimum power factor	480
2	Minimum shot weight	No
3	Minimum caliber	20 gauge / 20 bore
4	Maximum shotgun weight	No
5	Minimum trigger pull	No
6	Restriction on action types	No
7	Magazine length restrictions	No
8	Detachable magazines	Permitted
9	Capacity restrictions for initial load prior to the start signal	Max. of 9 rounds loaded Max. of 8 in the case of Rule 8.1.1.2
10	Speed loading devices	No
11	Modifications/attachments to loading port floor plate	Permitted but restricted, see below.
12	Compensators, sound and/or flash suppressors	No
13	Ports	No
14	Optical or Electronic sights	No
15	Barrel heat shields	Permitted
16	Max. distance of cartridges or reloading devices from body (excluding cartridges carried in or on the gun or sling)	50mm
17	Modifications allowed. Restricted – see below.	Permitted
18	Factory produced guns only (minimum 500 units)	Yes

Special Conditions:

19. Any complete shotgun produced by a factory and available to the general public.
20. Prototypes are specifically not allowed.
21. Changing caliber from the factory standard is specifically not allowed.

22. External modifications such as weights, or devices to control or reduce recoil are specifically not allowed, except for recoil pads fitted to the rear face of the stock of the shotgun.
23. Modifications which are specifically allowed:
 - Replacement of: "Open Sights" with other "Open Sights", barrels, trigger mechanisms or components thereof, safety catches (ambidextrous safety catches are approved), action release buttons, cocking levers, magazine tube followers and/or springs, fore-ends and/or stock (pistol grip stocks are allowed).
 - Feed ramps as replacements of the carrier release button (Remington 1100 and 1187).
 - Extended magazine tubes.
 - Enlargement and/or rounding of ejection ports; enlargement and/or rounding of loading ports.
 - Checkering of frames, stocks and fore-ends.
 - Cosmetic enhancements that do not give a competitive advantage such as custom grips, plating, etc.
24. Internal modifications to improve reliability are allowed.
25. Additional cartridge loops or clips, specifically including side saddles, may be fitted to the stock, fore-end, receiver or sling (providing they do not compromise any safety issues).

Standard Manual Division

1	Minimum power factor	480
2	Minimum shot weight	No
3	Minimum caliber	20 gauge / 20 bore
4	Maximum shotgun weight	No
5	Minimum trigger pull	No
6	Manual action only	Yes
7	Magazine length restrictions	No
8	Detachable magazines	Permitted
9	Capacity restrictions for initial load prior to the start signal	Max. of 9 rounds loaded Max. of 8 in the case of Rule 8.1.1.2
10	Speed loading devices	No
11	Modifications/attachments to loading port floor plate	Permitted but restricted, see below.
12	Compensators, sound and/or flash suppressors	No
13	Ports	No
14	Optical or Electronic sights	No
15	Barrel heat shields	Permitted
16	Max. distance of cartridges or reloading devices from body (excluding cartridges carried in or on the gun or sling)	50mm
17	Modifications allowed. Restricted – see below.	Permitted
18	Factory produced guns only (minimum 500 units)	Yes

Special Conditions:

19. Any complete manual action shotgun (pump/slide/break-open) produced by a factory and available to the general public.
20. Prototypes are specifically not allowed.
21. Changing caliber from the factory standard is specifically not allowed.

22. External modifications such as weights, or devices to control or reduce recoil are specifically not allowed, except for recoil pads fitted to the rear face of the stock of the shotgun.
 23. Modifications which are specifically allowed:
 - Replacement of: "Open Sights" with other "Open Sights", barrels, trigger mechanisms or components thereof, safety catches (ambidextrous safety catches are approved), action release buttons, cocking levers, magazine tube followers and/or springs, fore-ends and/or stock (pistol grip stocks are allowed).
 - Extended magazine tubes.
 - Enlargement and/or rounding of ejection ports; enlargement and/or rounding of loading ports.
 - Checkering of frames, stocks and fore-ends.
 - Cosmetic enhancements that do not give a competitive advantage such as custom grips, plating, etc.
 24. Internal modifications to improve reliability are allowed.
 25. Additional cartridge loops or clips, specifically including side saddles, may be fitted to the stock, fore-end, receiver or sling (providing they do not compromise any safety issues).
-